



ZTIPD-Z8M

camera	
image sensor	4K 1/2.8" sony
LUX	COLOR 0.05Lux@F1.2; B/W 0.005Lux@F1.2;
S/N	≥50db(AGC OFF)
WDR	DWDR; > 80db
lens	
Focal Length	2.8mm
Lens Type	Fixed-focal
Angle of View (H)	106.9°
Angle of View (V)	56.9°
Angle of View (D)	127.9°
Video	
Coding Format	H.265/H.264
resolution	main :3840*2160, 1-15FPS/S 2880*1664, 2560*1440, 2304*1296, 1920*1080, 1280*720, 1-15FPS/S sub : 704*576, 800*448, 640*480, 640*360, 352*288, 1-15FPS/S
Video Coding Compression	128Kbps-8192bps continuous adjustable
Subtitle Overlay	Support Channel Name, Date & Time, Resolution & 4 lines characters adding
Data Transmission & Storage	
Data Record	Video, picture
Protocol	All Net Connect / ONVIF 2.6
Mobile	Support IOS ,Android
Browser	Support IE6.0 and above browser Client Browser
IR Board	
The product name	IR light led
lamp cup piecs	2 piecs
Voltage	12V DC
warm light distance	up to 30M
general	
Power	DC12V /POE
housing	Size: 60 Metal / white
Dimensions (Ø x H)	109.4 × 95.5
Weight	Weight (net) Approx. 0.290KG
Operating	- 20 °C ~ 55 °C (-4°F~131°F)
Environment	Humidity: less than 95 % (non-condensing)

MADE IN EGYPT