

Resin Rock Speaker

ZTPA-20WGARDEN



Description

ZTPA-20WGARDEN is a landscape garden speaker with built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers.


The high-class resin enclosure is of rock shape and weatherproof. It is with heavy damage proof finish. Easy and secure installation in outdoor area.

It is an ideal choice for industrial and commercial applications in outdoor areas, such as train station, shopping mall, parking area and factory where background music and paging are needed.

Specification

Full-range	6.5"×1
Rated	20W
Max Power	40W
Line Voltage	70/100V
Sensitivity(1M,1W)	87±2dB
Max SPL(1M)	100±2dB
Freq. Resp.	100Hz-15.5kHz
Dimension(L×W×H)	380×250×320mm
Weight	5kg

DIMENSIONS



Features

- IP6 waterproof level
- Max SPL: 100±2dB
- 6.5"×1 full-range driver
- high-class resin material
- High sensitivity: 87±2dB
- Heavy damage proof finish
- Built-in 100v/70v transformer
- Wide Freq.Resp.: 100Hz-15.5kHz
- Power taps at 10W-20W@100V
- Landscape garden loudspeaker

Installation

1. Setup a foundation like a round platform with concrete and set 3 screws (8mm) stretching out 3cm in it as shown above after concrete acidify continue;
2. Connect audio broadcasting wire to the speaker terminals according to the table below;


Power Line Voltage	70V	100V
Terminals		
Red---Blue	10W	20W
Red---White	20W	40W (Notice)

3. Fix the speaker system with 3 nuts on screws of the foundation;
4. Finally, examine whether it is steady.

Notice: While broadcasting wire is quite long and with high impedance only.

FREQ. RESPONSE

(dB SPL, 1W, 1m)



DISTORTION

(THD< 1.5% 1W, 1m, 2000Hz~10kHz)

