



ZTEG-B5M

- **1/2.7 inch cmos sensor**
- **5MP (2592x1944)**
- **Color : 0.1Lux@ (F1.2, AGC ON 0Lux with IR**
- **Black & White : 0.001Lux@ (F1.2, AGC ON, 0Lux with IR**
- **3D DNR, digital WDR, HLC, BLC, defog**
- **lens Focal Length 3.6mm**
- **UP TO 30M IR**
- **IP 67**



SPECIFICATION

Model Specifications	ZTEG-B5M
Camera	
Image Sensor	1/2.7 inch cmos sensor
Min. Illumination	Color : 0.1Lux@ (F1.2, AGC ON 0Lux with IR Black & White : 0.001Lux@ (F1.2, AGC ON) , 0Lux with IR
Shutter Time	1/50(1/60) seconds to 1/10,000 seconds
Lens	
Focal Length	3.6mm
"Lens Type	"Fixed-focal
"Angle of View (H)	83°
Angle of View (V)	45°
Angle of View (D)	100°
VIDEO	
Video output	5MP@XVI ; @AHD/TVI/CVI ; CVBS
Day & Night	ICR filter with auto switch
IR Board	
infrared distance	Up to 30m
menu	
AGC	Support
D/N Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MWB
BLC	Support
DWDR (Digital	Support
Language	English
Functions	Brightness, Sharpness, DNR , Mirror, Smart IR
general	
Power	"DC12V/2A input, power consumption:≤3W,
housing	Size: 60 Metal / white
Operating	-30 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or
Power Supply	12 VDC ±25%
Protection Level	IP67
DIMENSION	
DIMENSION	183×65.9×67.6

DIMENSION

