



ZERO  TECH

TAKING YOU FORWARD



ZTNX-32CH-FRPRO-HSRP

This series supports 32 CH 16MP/12MP /8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 1280 × 1024 / 960P /720P high-definition IP video input, which adopts the advanced SOC technique to ensure high-definition recording in each channel and realize outstanding robustness of the system. This series supports 32 CH IP input, simultaneous 16 CH playback, and 8K high definition display. So it can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



FEATURES

- Support 32 CH 16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024 /960P/720P/960H/D1/CIF IP input
- H.265S/H.265+/H.265/H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor/ POS / AI recording
- Playback: 16 CH simultaneous playback
- Search: time slice, time, event, tag, smart and target database search
- Support face detection and comparison
- Support multiple VCA (Video Content Analytics) events, such as region intrusion, tripwire, etc.
- Support OS information overlay on live view and playback
- Support RAID 0, 1, 5, 6, 10
- Express and flexible backup via USB, network and so on
- Preview, record, playback, backup and remote access are supported
- DHCP, DDNS, PPPoE network protocol, etc.
- Compatible with third-party IPCs, such as ONVIF, Hikvision, etc.
- Remote control via Web Client or CMS : preview, playback, backup PTZ and configuration
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 8K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS



4K Output



HD IPC



DDNS



Network



PTZ



Audio



MIC



Mobile



CMS



USB



Mouse



E-mail



STD



FR



VCA

SPECIFICATIONS

Model		
System	OS	Embedded Linux
Video	IP Video Input	32
	Network Bandwidth	Incoming: 320Mbps Outgoing: 320Mbps
	Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF
	Output	HDMI1: 7680×4320@60 7680×4320@30 3840×2160@60 3840×2160@30 1920×1080 1280×1024 1024×768 (When the resolution of HDMI1 output is 8K, HDMI2 is unavailable) HDMI2: 3840×2160@60 3840×2160@30 1920×1080 1280×1024 1024×768 HDMI3: 3840×2160@60 3840×2160@30 1920×1080 1280×1024 1024×768 HDMI4: 1920×1080 1280×1024 1024×768 VGA×1: 1920×1080 1280×1024 1024×768 (VGA and HDMI1 output the same video source)


	Multi-screen Display	Main output: 1/4/6/8/9/13/16/25/32/36 AUX output 1: 1/4/6/8/9/13/16/25/32/36 AUX output2: 1/4/6/8/9/13/16 AUX output 3: 1/4/6/8/9/13/16 Max. 96(32+32+16+16)
	Compression	H.264/H.265/H.265+/H.265S
Audio	Network input	32
	Local Input	RCA×1 (for two-way talk)
	Local Output	RCA×1
	HDMI Audio Output	Support
Record	Compression	G.711(U/A)
	Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF
Playback	Frame Rate	N:30fps P:25fps
	Simultaneous Playback	16CH
	Search	Time slice/time/event/tag/smart search
Decoding Capability	Function	Play, pause, FF, Rewind, digital zoom, previous frame, next frame, etc.
	Live View	1×16MP@30 / 4×12MP (only available for main output)
Alarm	Playback	1×16MP@30 / 4×8MP(only available for main output)/
	Mode	Manual, sensor, motion, exception, smart events, etc.
	Input	16CH
	Output	8CH
Face	Triggering	Record, snapshot, preset, e-mail, etc
	Face Detection	32CH
	Face Performance (AI by IPC)	4CH
	Face Detection (AI by Device)	16CH
	Face Match Performance	36 pictures/second
	Comparison Capability	32 libraries 10000 face pictures
	Face Picture Database	Search by picture is supported
	Face Picture Search	Add, modify, delete and search face pictures
	Database Management	Add face pictures through APP, WEB and external import
	Face Picture Adding	Supports successful face recognition alarm and stranger match alarm
	Face Picture Comparison	Track display on a map
	Track	Bar graph
	Statistical Graph of Information	Statistics by day, week, month, quarter as well as customized time period
Video Structure Analysis	Statistical Mode of Information	32CH
	Human/Vehicle Classification (AI by IPC)	8CH
	Human/Vehicle Classification (AI by Device)	Yes
	Human/Vehicle Attribute Analysis (AI by IPC)	Yes
Fisheye Access	Yes	




	Interface	RJ45 10/100/1000Mbps ×2
	Client Connection	Max. 128 users access
Mobile Device	OS	iOS, Andriod
Storage	HDD Interface	SATA× 8 max 16TB per HDD
	RAID Type	RAID0,1,5,6,10
	E-SATA Interface	2
Port	USB	USB3.0× 1 USB2.0 × 3(Front:2)
	RS485	Yes (full-duplex)
	RS232	Yes
	Reset	Yes
	12V Output	Yes (1A)
	Remote Controller	Optional
	Others	Power
Consumption		≤50W (without HDD)
Dimensions		560×437.2×88mm
Certificate		CE,FCC
Environmental Protection		Directive EU RoHS, WEEE(2012/19/EU) , Directive 94/62/EC and REACH(EC1907/2006)
Working Environment		-10~50°C; Humidity: 10%~90%

REAR PANEL

REAR PANEL FOR SINGLE POWER SUPPLY



REAR PANEL FOR REDUNDANT SERIES



DIMENSIONS

