

5MP 30x IR Anti-Corrosion Network Bullet Camera



SN-CHP8650EBR(-K)-Z30-SSFF

Key Features

- ✚ 1/2.8" STARVIS™ CMOS
- ✚ Max. 5MP(2592x1944) @25/30fps resolution
- ✚ 30x optical zoom, 16x digital zoom
- ✚ Supports detection and capture of faces, humans, and vehicles, as well as smoke and flame detection.
- ✚ Intelligent analysis: intrusion, single line crossing, double line crossing, loitering, wrong-way, illegal parking, and people counting.
- ✚ IR distance up to 200 m
- ✚ -K: Support fiber optical interface
- ✚ 316L stainless steel enclosure, protecting cameras to be used in corrosive environments
- ✚ IP68 water resistant

Specification:

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Max. Resolution	5MP, 2592(H) × 1944(V)
Electronic Shutter	Auto/Manual, 1/5 to 1/100,000s
Min. illumination	Color: 0.07 Lux @ (F1.6, AGC ON), B/W: 0.02 Lux @ (F1.6, AGC ON)
Day & Night	Auto (ICR)
Wide Dynamic Range	True WDR
Wiper	Support
Lens	
Focal Length	5.3 to 159 mm, 30x Optical Zoom
Max. Aperture	F1.6 to F4.3
Angle of View	H: 56.3° to 2.7°, V: 42.4° to 2.0°
Zoom Speed	Approx. 2.5 s
Digital Zoom	16x
Iris Control	Auto/Manual
Focus Control	Auto/Manual/Semi-automatic
DORI Distance	
Detection	104 to 3,120 m (341.2 to 10,236.2 ft)
Observe	41.6 to 1,248 m (136.5 to 4,094.5 ft)
Recognize	20.8 to 624 m (68.2 to 2,047.2 ft)
Identify	10.4 to 312 m (34.1 to 1,023.6 ft)
DORI (Detect, Observe, Recognize, and Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances.	
Illuminator	
Illuminator Type	IR
Illumination Distance	Up to 200 m (656.17 ft)
Illumination On/Off Control	Auto/Manual
IR wavelength	850 nm



Intelligent Analytics

Multi-Object Detection

Supports face, human, vehicle detection and capture.
Supports multiple frame modes: Full Frame, Four-corner Frame, and Mosaic.
Support

Smoke and Flame Detection

Intelligent Analysis

Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way, Illegal parking, Smart Motion Detection
(support the accurate detection of vehicle and human)
Support

People Counting

Video and Audio

Streaming Capability

3 Streams

Stream/Frame Rate

Stream1: 2592×1944, 2592×1520, 1920×1080, 1280×720 @25/30fps
Stream2: D1, VGA, CIF @25/30fps
Stream3: VGA, CIF, QVGA @25/30fps

Bit Rate Control

CBR/VBR

Bit Rate

Stream1: 200 kbps to 12 Mbps
Stream2: 100 kbps to 6 Mbps
Stream3: 100 kbps to 3 Mbps

Smart Encoder

Support

Region of Interest (ROI)

Support

Audio Compression

G.711 A-law, G.711 μ -law, RAW_PCM

Audio Bit Rate

64 kbps (G.711), 128 kbps (RAW_PCM)

Image

Image Adjustment

Brightness, Sharpness, Contrast, Saturation adjustable

Scene Setting

Indoor, Outdoor, Mirror

Exposure Mode

Auto, Manual, Shutter priority, Iris priority

White Balance

Auto, Tungsten, Fluorescent, Daylight, Shadow, Manual

Day/Night Setting

Auto, Day, Night, Timer

Noise Reduction

2D/3D DNR

Image Enhancement

HLC, BLC, Defog, WDR, Anti-shake

Privacy Masking

Support 8 zones, mask color configurable

Event

Alarm Triggers

IVS, Motion detection, Alarm input, Network alarm, Disk alarm, Day/Night switch alarm, Abnormal sound detection

Event Actions

Alarm record, SMTP upload, FTP upload, Alarm output, Audible alarm output

Network

Protocols	IPv4/IPv6, HTTP/HTTPS, DNS, DDNS, DHCP, PPPoE, RTSP/ RTP/RTCP, TCP/UDP, NTP, ARP, UPnP, FTP, SMTP, QoS, ICMP, IGMP, SMTP, 802.1x, SNMP, Multicast
Interoperability	ONVIF (Profile S/T/G/M), SDK, CGI
Max Concurrent Streams	10 channels
User/Host Level	32+ users, 3 levels: Administrator, Operator, Media user
Security	IP address filter, HTTPS, Illegal login lock, IEEE 802.1x
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge


Interface

Network Interface	1 × RJ-45, 10/100 Mbps self-adaptive Ethernet port
Fiber Optical	-K: 1 single module fiber interface
Audio Interface	1ch Input, 1ch Output
Alarm Interface	2ch Input, 1ch Output
RS-485	Support
CVBS Interface	Support
SD Card Slot	Built-in, up to 256GB
Reset Button	Built-in

General

Language	English, Chinese, Traditional Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian, Japanese, Korean. Default: English
Power Supply	100 to 240VAC
Power Consumption	Less than 36W
Operating Temperature	-40°C to 60°C (-40°F to 140 °F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP68
Material	SUS316L
Dimensions	523.5 × 405.6 × 220.6 mm (20.6 × 16 × 8.7 inch)
Net Weight	18 kg (39.68 lb)

Dimensions (mm)



Accessories

Optional:



Wall Mount



Pole Mount



Corner Mount



Junction Box



Washing Tank



Flexible Tube

