




# ZTIPD-EGAI2M-AF

- Starlight
- 2MP ( 1920 x 1080 ) @30fps
- Support smart H.265/H.264 coding
- ICR auto switch, true day / night
- 30 ~ 50m IR night view distance
- Motorized zoom lens
- 3D DNR, true WDR, HLC, BLC, Defog, Smart IR and ROI coding
- Support corridor mode
- Support image distortion correction
- 1CH built-in MIC;1CH audio output and 1CH audio input
- 1CH alarm input and 1CH alarm output
- IP67 & IK10
- Built-in micro SD card slot, up to 256GB
- Intelligent analytics: Perimeter Protection,Target Counting, Exception Detection,Face Detection,etc
- DC12V/PoE power supply
- P2P function optional



Motion detection



AWB



HLC



WDR



DEFOG



POE



H.265



BLC



IP67



IK 10



VCA



-30°~-60°



DAY & NIGHT




**MADE IN EGYPT**

## SPECIFICATIONS

Model	ZTIPD-EGAI2M-AF
<b>Specifications</b>	
<b>Camera</b>	
Image Sensor	1 / 2.8" CMOS
Image Size	1920 × 1080
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Auto Iris
Min. Illumination	0.0038 lux@F1.4,AGC ON; 0 lux with IR 0.0028 lux@F1.2,AGC ON; 0 lux with IR
Lens	2.8-12mm@F1.4, motorized
Field of View	Horizontal: 103°~32°; Vertical: 70.5°~18.3°; Diagonal: 110.6°~36.4°
Lens Mount	Φ14
Day & Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~345°; Tilt: 0°~77°; Rotation: 0°~345°
<b>Image</b>	
Video Compression	Main stream: Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream	60Hz: 1080P/720P (1~30fps); 50Hz: 1080P/720P (1~25fps)
Sub Stream	60Hz: 720P/D1/CIF/480×240 (1~30fps); 50Hz: 720P/D1/CIF/480×240 (1~25fps)
Third Stream	60Hz: D1/CIF/480×240 (1~30fps); 50Hz: D1/CIF/480×240 (1~25fps)
Bit Rate	64 Kbps ~ 6 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
<b>Interface</b>	
Network	Rj45
Video Output	CVBS (BNC × 1)
Audio	1CH audio input; 1CH audio output; Built-in MIC × 1
Storage	Built-in micro SD card slot; up to 256GB
Reset	Yes
Alarm	1CH alarm input; 1CH alarm output
<b>Intelligent analytics (Smart Event)</b>	
Perimeter Protection	Creation of virtual lines and enter / exit zone creation (human/motor vehicle/non-motor vehicle classification)
Target Counting	Line crossing human/motor vehicle/non-motor vehicle counting object tracking , appear /disappear
Exception Detection	Scene change, video blur and video color cast detection
Face Detection	Face detection and face capture
<b>Functions</b>	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, FTP, PPPoE, DDNS, SMTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	Support ONVIF (Profile S/T/G)
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, cable disconnection

PoE	Yes , IEEE802.3af
IR Distance	30 ~ 50 m
Ingress Protection	IP67 & IK10
<b>Others</b>	
Power Supply	DC12V/PoE
Power Consumption	< 8W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions ( mm )	Φ 141 × 100.2
Weight ( net )	Approx. 0.93KG
Installation	Ceiling mounting; Wall mounting

## DIMENSIONS



## AVAILABLE ACCESSORIES

